



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Pile Weight:	28 oz/yd <sup>2</sup> (949 g/m <sup>2</sup> )
Finished Pile Thickness:	.106" (2.69 mm)
Stitches Per Inch:	9.5 (37.40 per 10 cm)
Dye Method:	Solution Dyed
Fiber Type:	Duracolor® Tricor Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	EcoSentry Soil Protection
Density:	9,509
Weight Density:	266,264
Backing Material:	EcoFlex NXT
Installation Method:	Monolithic, Monolithic Stepping, Plank Half Lap, Basket Weave, Half Lap, Brick Ashlar, Random, Herringbone
Size:	12" x 36" (.3048 m x .9144 m)
Pattern Repeat:	Not Applicable

**SUSTAINABILITY**

Pre-Consumer Recycled Content:	57%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP1171
Declare Label:	Declared Red List Free

**PERFORMANCE**

Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Heavy
GSA Stain Release Rating:	Pass

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



937  
Frosted Shield



941  
Goldspeck



945  
Silva



952  
Orange Sea



954  
Everbloom



956  
Iceland Moss



963  
Firedot



975  
Felt Finish



976  
Dust Cloud